



AMI Series

Magnetic Stirrers

Single-position or 4-position illuminated magnetic stirrer,
particularly indicated for titrations



Resistant and Easy-to-use

Illuminated magnetic stirrer particularly useful for titrations. The illuminated surface facilitates the visualization of particles and color changes. It guarantees excellent speed control (electronic), even at low speed.

- Speed regulation up to 1100 rpm
- Excellent electronic speed control, even at low speed
- 4-position model provides independent speed regulation
- Possibility to adjust the illumination brightness



INSTRUMENT - CODE

AMI	100-240 V / 50-60 Hz	F204A0167
AMI 4	100-240 V / 50-60 Hz	F204A0168

TECHNICAL DATA

	AMI	AMI 4
CONSTRUCTION MATERIAL	Epoxy painted metal structure	Epoxy painted metal structure
MODELS	Single-position	4-position
STIRRING VOLUME	up to 5 L	up to 5 L
DISTANCE BETWEEN STIRRING POSITION CENTRES	-	150 mm
ELECTRONIC SPEED REGULATION	Up to 1100 rpm	Up to 1100 rpm
SPEED CONTROL	Excellent speed control even at low revolutions	Excellent speed control even at low revolutions
STIRRING SYSTEM	High-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation	High-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation
DIMENSION (WXHxD)	150x55x270 mm (5.9x2.2x10.6 in)	600x55x270 mm (23.6x2.2x10.6 in)
POWER	1.2 W	4.8 W
WEIGHT	1.2 Kg (2.6 lb)	4.0 Kg (8.8 lb)



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 180 1755 7329
velpchina@velp.com