

NEW

Advanced Autoclave

Advanced Autoclave

Basic configuration : 2 hoses, autoclave gloves, tong gloves, 2 baskets, printer
Additional options : Additional basket available for purchase, dedicated distilled water

- Automatic discharge of high temperature pressure 3 times, removal of air pockets
- X-ray inspection of all chamber welds
- Heater overheating prevention sensor and automatic water level control sensor
- Door sensor (Gating)
- Automatic replenishment of distilled water
- Printer interface
- Built in printer

	BF-45X	BF-60X	BF-90X	BF-110X
Volume	45L	60L	90L	116L
heater	3kw	3kw	4.5kw	4.5kw
sensor	PT-100(Sterilization only)			
error	±0.5°C			
display	LCD display			
Voltage	220V			
set	50-134°C			
texture	SUS304			
GW/NW	125/110kg	130/112kg	145/114kg	156/129kg
chamber size	Φ 350X400	Φ 350X525	Φ 400X625	Φ 450X650
basket size	Φ 320X350 (1ea)	Φ 320X240 (2ea)	Φ 360X280 (2ea)	Φ 410X300 (2ea)
external size	(W)698X (D)498X (H)940mm	(W)698X (D)498X (H)1,110mm	(W)770X (D)570X (H)1,185mm	(W)788X (D)588X (H)1,255mm
packaging size	(W)790X (D)610X (H)1,130mm	(W)800X (D)600X (H)1,230mm	(W)840X (D)610X (H)1,310mm	(W)870X (D)650X (H)1,380mm

Automatic discharge of high temperature pressure
3 times, removal of air pockets



Air Filter → Prevention of backflow



vapor reduction device



LCD touch display



BF-90X